

| ECN No. | SYM | REVISION | DATE | REVISOR | APPROVED |
|---|---|---|---|---|---|
| | 1 | | | | |
| | 2 | | | | |


AIR INLET 3/4"  AIR OUTLET 3/4"





## OPERATING CONDITIONS

FLOW RATE : 1.0 N㎥/min
RATED INLET AIR PRESSURE : 7 kg/㎠
MAXIMUM INLET AIR PRESSURE : 9.9 kg/㎠
RATED INLET AIR TEMPERATURE : 55 ℃
RATED AMBIENT AIR TEMPERATURE : 38 ℃
AIR FILTER : 20A 32 & 31
DEW POINT : 10 ℃




# REFRIGERATED AIR DRYER (SCT-10)

| MARK | PARTS | PARTS NO. | Q'TY | MATERIAL | DESCRIPTION | WEIGHT |
|---|---|---|---|---|---|---|
| | | | | | | |

| | | | |
|---|---|---|---|
| APP. S.LEE | SCALE 1 : 8 | SMD KOREA.CO.,LDT KOREA | |
| CHK. D.W.KIM | SIZE A3 | DWG. NAME REF. AIR DRYER (Air Cooled Type) SCT-10 OUTSIDE DWG. | |
| DRW. D.W.KIM | REF.DWG.NO. | | |
| DATE 2015.12.10 | UNIT mm | DWG. NO. SK-T010-001-0 | SHEET 1/1 |